

Non-electric water softeners

+ Dual tank: guaranteed 24/7 continuous supply of soft water

+ Non-electric

+ Suitable for both hot and cold water

Hard water causes scaling of heating elements in electrical appliances, and leads to both overconsumption of electricity and increased maintenance costs. Scaling also impacts your productivity, as your appliance will run a higher risk of loss of performance, and in worst case break down.

Non-electric dual tank

With these innovative non-electric and dual-tank water softeners from Granuldisk, you no longer have to worry.

Hot and cold water treatment

Simply connect to any water inlet temperature ranging from 2-65 °C.



Compact and durable

Thanks to their compact design, Granuldisk water softeners are ideal when space is limited, and has a tough and durable cabinet to better withstand rough treatment.

Works with all Granuldisk® products

Granuldisk water softeners are adapted to fit all of our range. Choose the size that best corresponds with your needs.

Art. number: 28145

8 kg salt capacity - fits X2 Lean Wash Center*


Art. number: 20197

18 kg salt capacity - fits with all Granuldisk® products

Non-electric water softeners for hot or cold water

Specifications	Art. number: 28145	Art. number: 20197
Salt capacity	8 kg	18 kg
Regeneration @ 2bar	34 liters - 11 min.	24 liters - 11 min.
Temperature range	2-65° C	2-65° C
Dynamic pressure	2.5 – 8.5 bar	2.5 – 8.5 bar
pH range	5 – 10	5 – 10
Weight (shipping/operating)	21/39 kg	27.2/49.9 kg
Connections		
Electrical power	None	None
Inlet/Outlet connections	Custom adaptor and bracket	Custom adaptor and bracket
Drain connection	0.375" tube	0.375" tube
Overflow connection	0.625" tube	0.625" tube

Art. number: 28145



Art. number: 20197

