

# Water softener

+ Dual tank: guaranteed 24/7 continuous supply of soft water

+ Non-electric

+ Suitable for both hot and cold water

---

Hard water causes scaling of heating elements in electrical appliances, and leads to both overconsumption of electricity and increased maintenance costs. Scaling also impacts your productivity, as your appliance will run a higher risk of loss of performance, and in worst case break down.

#### **Non-electric dual tank**

With an innovative dual-tank, non-electric water softener from Granuldisk, you no longer have to worry.

#### **Hot and cold water treatment**

Simply connect the softener to any water inlet temperature, ranging from 2-65 °C.



#### **Compact and durable**

The Granuldisk water softener is ideal for applications where space is limited, thanks to its compact design. The cabinet is tough and durable and can withstand rough treatment.

#### **Works with all Granuldisk® products**

The Granuldisk water softener can be connected and used with any model from the Granuldisk range.

**Article number: 20197**

# Specifications and technical details

## General

Width	356 mm
Depth	356 mm
Height	559 mm
Weight	27.2 - 49.9 kg

## Performance

Minimum Flow	2 l/min
Maximum Flow @ 1 Δ bar	34.5 l/min
Hardness as CaCO <sub>3</sub> (max)	513 mg/l

## Regeneration

Salt Used / Capacity	0.23 - 0.45 / 18 kg
Time	11 minutes
Volume	24 litres

## System

Media Volume	2 x 4.5 litres
Inlet/Outlet Connections	Custom
Maximum Temperature	2 - 65 °C
Inlet Pressure (min/max)	2.5 / 8.5 bar

